

AUDAC

► Features

- Design ceiling loudspeakers in modern metal housing, with an aluminium grill
- True-to-nature sound reproduction
- Quick and easy installation
- Discreet mount in wall or ceiling
- Wide dispersion sound
- High efficiency
- Shielded neodymium magnet
- Built-in self resetting protection circuit

► Applications

- Offices
- Boutiques
- Shops
- Hotel rooms
- Private houses



The CS2.1 Cuban speaker features a 2" full range loudspeaker with a shielded neodymium magnet, which is capable of producing up to 10 W RMS, with a maximum of 20 W.

The uniquely designed CUBAN square loudspeakers are flush-mounted ceiling and/or wall speakers, which provide high-quality, wide-dispersion sound while remaining as discreet as possible. Efficiency is very important for inside-wall applications.

AUDAC's highly efficient Cuban series answers to this need with its ability to generate great sound with very little power. In fact, the Cuban speaker can generate sound from solid surfaces by utilizing only 3 to 25 watts.

These high-performance speakers have a small-perforated designer grill and are ideal for offices, boutiques, shops and hotel rooms. If used in combination with an AUDAC subwoofer, the sound will be even better. A built-in self resetting protection circuit guarantees a long lifetime without any loss of quality or power.

The Cuban speakers are made of a strong, metal housing with easy mounting springs for quick and comfortable installation.

The front shows a black aluminum grid embedded in an aluminum frame, giving the speaker a dazzlingly modern design. When an additional line transformer, like AUDAC's CTR06 or CTR24, is applied, the Cuban series speaker can be perfectly adapted in a 100V speaker line application.

► Specifications

SYSTEM SPECIFICATIONS	
Max. power	20 W
RMS power	10 W
Frequency response -3dB	250 Hz - 18 kHz
Sound pressure 1 W / 1m	85 dB
Sound pressure max W / 1m	95 dB
Impedance	8 Ohm
PRODUCT FEATURES	
Dimensions (Width x Height x Depth)	102 x 102 x 90 mm
Weight net	590 g
Driver	2"
Construction	Metal housing
Connection cable length	370 mm
Mounting	Mounting springs
Front finish	Brushed aluminium frame with Black aluminium grill
Colour	Brushed aluminium + Black
Cut-out measurement	85 x 85 mm
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight & volume	620 Kg - 0.062 Cbm
Accessories	CTR06: 100 V Line transformer 6 W CTR24: 100 V Line transformer 24 W
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products	