

CS75

Ceiling Speaker

AUDAC

► Features

- High-quality 2-way ceiling loudspeaker
- Very attractive design
- Detachable aluminium grill
- 3 different power tapings
- True-to-nature sound reproduction
- Quick and simple mounting
- Very wide frequency response
- Easy to hide away

► Applications

- Public buildings
- Business offices
- Warehouses
- Shops
- Hotels
- Restaurants



The CS series loudspeakers are AUDAC's ceiling speakers, designed to be used in any possible application.

Wherever sound is needed without obvious speakers, or in larger buildings where the sound has to be spread over an enormous space, the CS Series speakers will offer the best solution.

The use of high quality components, combined with the application of a standard 100V line transformer, makes the CS series a range of speakers that can be used in any situation. Even if it's a standard low impedance Hi-Fi installation or a larger 100V PA system.

The CS75 is an extremely high-quality ceiling loudspeaker for installation purposes..

It is a 2-way loudspeaker, with a diameter of 5 1/4" for the low frequencies, and a tweeter, mounted in the center, for the high frequencies.

This ensures a brilliant reproduction of all kinds of music.

Because of the moisture-proof treatment and the aluminium grill, the loudspeaker can be placed outdoor or in damp rooms.

Below the detachable grill, there are four screws for a quick and simple attachment of the unit.

The removable grill and housing of the speaker can be painted, to blend in with the structure the speaker is built in. With these speakers comes an easy cut-out template to accomplish easy installation.

Available in White, Black (/B) and 16 Ohm version (/D).

► Specifications

SYSTEM SPECIFICATIONS		
Max. power		60 W
RMS power		30 W
Line Transformer Power Tap 1		24 W / 416 Ohm
Line Transformer Power Tap 2		12 W / 832 Ohm
Line Transformer Power Tap 3		6 W / 1666 Ohm
Frequency response -3dB		Fo Hz - 20 kHz
Sensitivity 1W/1m		90 dB
Sound pressure max W / 1m (8 Ohm)		104 dB
Sound pressure max W / 1m (100 V)		104 dB
Impedance		8 Ohm
Crossover		Passive built-in
PRODUCT FEATURES		
Dimensions (Width x Height x Depth)		Ø 205 x 90 mm
Weight net		1.5 Kg
Drivers (Coaxial)	HF	1"
	LF	5 1/4"
Construction		ABS housing
Mounting		4 Screws clamps
Cut-out measurement		Ø 167 mm
Built-in depth		100 mm
Front finish		White aluminium grill
Colour		White (RAL 9010) - CS75
		Black (RAL 9005) - CS75/B
SHIPPING & ORDERING		
Packaging		Carton box
Shipping weight & volume		1.58 Kg - 0.0055 Cbm
Accessories		Foam inlay
		Cut-out template

*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products